

Antenna Type	Antenna Type	Gain (2.4GHz)	Gain (5GHz)	Horizontal Beamwidth	Vertical Beamwidth	Type of Connectors	No. of Units per AP	AP Compatibility	Use Case
<a href="#">M6120130MP1D6006W</a>	Directional			120°	12°	N-Style Plug	1	O-235E	The antenna provides a high gain with narrow vertical and wide horizontal beamwidths which allow concise coverage for aisles and make it ideal for warehouse deployments
<a href="#">M6011012MP1D63607</a>	Directional	13 dBi	13 dBi	35°/30°	35°/30°	N-Style Plug	1	O-235E	High-gain, narrow-beam antennas ideal for high-density deployments
<a href="#">M6040070O10007</a>	Omni	4 dBi	7 dBi	360°	35°/25°	N-Style Plug	6	O-235E	Rubber-ducky antenna which directly fits into the AP; suitable for wide variety for outdoor and indoor deployments.
<a href="#">M6040070O10007B</a>	Omni	4 dBi	7 dBi	360°	35°/25°	N-Style Plug	6	O-235E	Compact rubber-ducky antenna which directly fits into the AP; suitable for wide variety for outdoor and indoor deployments.
<a href="#">OP24516DS-91NM</a>	Omni	2.8 dBi	6.5 dBi	360°	66°/30°	N-Style Plug	1	O-235E	Outdoor deployments, Challenging indoor deployments such as warehouse, manufacturing environments.
<a href="#">M6060060MO1D3607O</a>	Omni	6 dBi	6 dBi	360°	35°/25°	N-Style Plug	1	O-235E	Outdoor deployments including P2P links, Challenging indoor deployments such as warehouse, manufacturing environments.
<a href="#">M6060060P3D63607V</a>	Directional	6 dBi	6 dBi	80°/45°	80°/45°	N-Style Plug	1	O-235E	Challenging Outdoor and indoor deployments such as stadiums, auditoriums, warehouse, manufacturing environments, especially where ceilings are high.
<a href="#">M060060M1D43607C</a>	Omni	5 dBi	6 dBi	360°	45°/20°	N-Style Plug	1	O-105E	Outdoor deployments including P2P links, Challenging indoor deployments such as warehouse, manufacturing environments.
<a href="#">M6060060O23607O</a>	Omni	6 dBi	6 dBi	360°	40°	N-Style Plug	1	O-105E	Outdoor deployments, Challenging indoor deployments such as warehouse, manufacturing environments.
<a href="#">M6060060P1D43607T</a>	Directional	5 dBi	6 dBi	105°/125°	60°/70°	N-Style Plug	1	O-105E	Challenging outdoor and indoor deployments such as stadiums, warehouse, manufacturing environments, especially where ceilings are high. Recommended for sectoral pole/mast mounted deployments also.
<a href="#">M6080060DP33607</a>	Directional	8 dBi	6.5 dBi	60°/65°	65°/70°	N-Style Plug	1	O-105E	Challenging outdoor and indoor deployments such as stadiums, warehouse, manufacturing environments, especially where ceilings are high. Recommended for sectoral pole/mast mounted deployments also.

Antenna Type	Antenna Type	Gain (2.4GHz)	Gain (5GHz)	Horizontal Beamwidth	Vertical Beamwidth	Type of Connectors	No. of Units per AP	AP Compatibility	Use Case
<a href="#">M60250401D3620PV</a>	Omni	3 dBi	4.5 dBi	360°	55°/60°	RPSMA Plug	1	C-230E, C-130E	Indoor deployments such as warehouse, manufacturing environments.
<a href="#">TWS244950-RPSMA-W</a>	Omni	3.5 dBi	6 dBi	360°	70°/50°	RPSMA Plug	6	C-230E, C-130E	Rubber-ducky antenna which directly fits into the AP; suitable for wide variety for indoor deployments.
<a href="#">M040030D33620JB6</a>	Directional	5 dBi	6 dBi	75°	75°	RPSMA Plug	1	C-230E, C-130E	Low profile antenna for wall/ceiling mount for auditoriums and other dense indoor environments (blends into existing room décor for “out of sight” coverage and capacity)
<a href="#">TWPRO-WIFIANT-APM</a>	Omni	5 dBi	6 dBi	75°	75°	RPSMA Plug	1	C-230E, C-130E	Antenna with rugged, RF-transparent IP-67-rated enclosure for protection against dust, water intrusion and strikes; ideal for challenging industrial applications such as manufacturing plants.
<a href="#">M6060060M01D3620O</a>	Omni	6 dBi	6.5 dBi	360°	35°/25°	RPSMA Plug	1	C-230E, C-130E	Challenging indoor deployments such as stadiums, auditoriums, warehouse, manufacturing environments, especially where ceilings are high.
<a href="#">M6060060D6D3620TM</a>	Directional	6 dBi	6 dBi	80°	90°	RPSMA Plug	1	C-230E, C-130E	Patch antenna wth rugged mounting solution for indoors/ outdoors and can be installed on poles or walls.
<a href="#">M6060060P1D63620</a>	Directional	7 dBi	6 dBi	115°/120°	70°/60°	RPSMA Plug	1	C-230E, C-130E	Antenna wth 10” Strong Arm Mount solution for indoors/ outdoors and can be installed on walls/masts.
<a href="#">M6025040M01D3620P</a>	Omni	2.5 dBi	4 dBi	360°	55°/60°	RPSMA Plug	1	C-230E, C-130E	Ceiling mount omnidirectional antenna with appealing design to maintain building decor. The antenna features a threaded plastic bushing and nut for simple ceiling tile mounting.
<a href="#">M6020020R1D0020</a>	Omni	2 dBi	3.5 dBi	360°	65°	RPSMA Plug	6	C-230E, C-130E	The small, compact size and lightweight structure make it easy to install, and blend into any environment.
<a href="#">M6085085D6D1820</a>	Directional	8.5 dBi	8.5 dBi	70°/56°	70°/56°	RPSMA Plug	1	C-230E, C-130E	Directional antenna, Ideal for sectoral coverage
<a href="#">M6060060P1D63620V</a>	Directional	6 dBi	6 dBi	80°/45°	80°/45°	RPSMA Plug	1	C-230E, C-130E	Antenna wth articulating mount, for demanding indoors/ outdoor deployments; it can be installed on poles or walls.