

RT-AX58U series (RT-AX3000)

AX3000 Dual band WiFi 6 Router

Features

- AX3000 WiFi 6 dual-band router (5GHz AX:2x2 + 2.4GHz AX: 2x2)
- AiProtection Pro powered by Trend Micro™
- ASUS AiMesh compatible
- USB 3.2 Gen 1 x 1 (USB 3.0) port for business applications



Specifications

| | |
|------------------|---|
| Network Standard | IEEE 802.11a, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac, IEEE 802.11ax |
| Product Segment | AX3000 ultimate AX performance |
| Coverage | Large homes |
| Data Rate | <ul style="list-style-type: none"> • 802.11b : up to 11 Mbps • 802.11a/g : up to 54 Mbps • 802.11ax (2.4GHz) : up to 574 Mbps • 802.11ax (5GHz) : up to 2402 Mbps |
| Antenna | External antenna x 4 |
| Transmit/Receive | 2.4 GHz 2 x 2 5 GHz 2 x 2 |
| Processor | 1.5 GHz tri core processor |
| Memory | 256 MB Flash, 512 MB RAM |

Specifications

| | |
|---------------------------|---|
| WiFi Technology | OFDMA (Orthogonal Frequency Division Multiple Access) Beamforming: standard-based and universal 1024-QAM high data rate 20/40/80/160 MHz bandwidth |
| Encryption | WPA3-PSK, WPA2 PSK , WPA PSK, WPA Enterprise , WPA2 Enterprise , WPS support |
| Firewall & Access Control | Firewall: SPI intrusion detection, DoS protection Access control Parental control, Network service filter, URL filter, Port filter |
| Management | UPnP, IGMP v1/v2/v3, DNS Proxy, DHCP, NTP Client, DDNS, Port Trigger, Port Forwarding, DMZ, System Event Log |
| VPN Support | IPSec Pass Through PPTP Pass Through L2TP Pass Through PPTP server OpenVPN server PPTP client L2TP client OpenVPN client |
| WAN Connection Type | Internet connection type : Automatic IP, Static IP, PPPoE (MPPE supported), PPTP, L2TP |
| Utilities | Router setup wizard; Firmware restoration; Device discovery ; printer setup utility |
| Ports | 1 x Gigabit WAN port 4 x Gigabit LAN ports 1 x USB 3.2 Gen 1 x 1 |
| Router Special Features | Multiple SSIDs, Parental Control |

Specifications

| | |
|----------|---|
| Features | <ul style="list-style-type: none"> Router app MU-MIMO Traffic Analyzer Adaptive QoS AiProtection Pro Parental Control Guest Network : VPN server : PPTP Server, IPSec server VPN client : PPTP client, L2TP client, OpenVPN client NAT Pass-Through :PPTP Pass Through, L2TP Pass Through, IPSec Pass Through, RTSP Pass-Through, H.323 Pass Through, SIP Pass Through, PPPoE relay Mac OS Backup Enhanced media server (AiPlayer app compatible) AiCloud personal cloud service 3G/4G data sharing Printer Server Download Master AiDisk file server IPTV support Roaming Assist OFDMA Beamforming AiMesh |
| Button | WPS Button, Reset Button, Power Switch |

Specifications

| | |
|----------------------|---|
| LED Indicator | Power x 1 2.4G x 1 5G x 1 LAN x 4 WAN x 1 |
| Power Supply | AC Input : 110V~240V(50~60Hz) DC Output : 19 V with max. 1.75 A current |
| OS Support | Windows® 11 Windows® 10 Windows® 8.1 Windows® 8 Windows® 7 Mac OS Linux |
| Operation mode | <ul style="list-style-type: none"> • Wireless router mode • Access point mode • Media bridge mode • Repeater mode |
| Dimensions (Product) | 22.4 x 15.4 x 16.0 cm (LxWxH) |
| Weight (Product) | 538g |